

4X2 HEAVY -

Container carrier 20ft

6X4 HEAVY -

Container carrier 20ft

* All versions could be needed

| ICRC Requirements | | SUPPLIER REPLY | |
|---|-----|----------------|-----------------|
| | YES | <u>NO</u> | <u>Comments</u> |
| Engine | | | |
| Maximum power: between 280 kW and 330 kW | | | |
| 6 cylinders diesel in line | | | |
| Emission level EEC EURO III to EEC EURO VI | | | |
| Liquid cooled engine | | | |
| Transmission | | | |
| Gearbox | | | |
| Automated manual gearbox (with automatic or semi- automatic mode). | | | |
| Between 12 and 16 speed forwards. | | | |
| Heavy duty gearbox reinforcement for extreme condition. | | | |
| Gearbox oil cooler (oil/engine coolant heat exchanger). | | | |
| Engine Brake | | | |
| Combination of exhaust brake retarder and engine | | | |
| compression brake coupled with service brake. | | | |
| Steering | | | |
| Power steering - hydraulic | | | |
| Left or Right-hand drive * | | | |
| Front axles | | | |
| Axle pivots with grease nipples | | | |
| Front load capacity: 9 t | | | |
| Rear axles | | | |
| Double reduction Integrated differential lock | | | |
| Rear load capacity: 32 t 6x4 | | | |
| Rear load capacity: 13 t 4x2 | | | |
| TIRES AND WHEELS | | | |
| 385/65R22.5 + 315/80 R22,5 OR 13 R22,5 (Premium brand) | | | |



| | | |
|--|------|--|
| Steel rims | | |
| Front wheel covers | | |
| Spare wheel in temporary fixing | | |
| | | |
| Brakes | | |
| Service brake: | | |
| Air compressor 900 I/min | | |
| Brake system with two independent circuits | | |
| Brake drums dust protection on rear brake | | |
| Electronic management of air production | | |
| Drying cartridge optimized by preventive maintenance | | |
| Silencer on pneumatic circuit | | |
| 2-line trailer braking device with ISO heads, automatic | | |
| (red), manual (yellow) | | |
| Trailer braking device on rear crossbar | | |
| Rear brake cylinders in high position | | |
| | | |
| EBS | | |
| Anti-lock Braking System (ABS) | | |
| Coupling of retarders and service brakes | | |
| Differential engagement management (if equipped) at | | |
| speed <10 km/h | | |
| Hill Start Assist. | | |
| Brake Performance Alert. | | |
| Emergency Brake Assist. | | |
| Emergency Stop Light. | | |
| | | |
| Parking brake | | |
| Automatic electronic parking brake | | |
| Parking brake with spring-loaded cylinders | | |
| Reinforced parking brake | | |
| | | |
| Adjustments | | |
| Automatic brake lining slack compensation | | |
| | | |
| Emergency brake | | |
| Provided by the independence of the circuits of the main | | |
| device | | |
| | | |
| <u>Cabin</u> | | |
| External | | |
| Night & Day cab * | | |



| Electro-galvanized sheet metal cab, cataphoretically treated | | |
|--|--|--|
| Body color: white | | |
| 4-point air suspension cabin | | |
| 2 remote-controlled heated mirrors | | |
| 2 wide-angle mirrors | | |
| Docking mirror Mirrors for overall length of vehicle 2.550 | | |
| m | | |
| Folding rear view mirror | | |
| Tire pressure monitoring system | | |
| Sun visor | | |
| Laminated tinted windscreen | | |
| Without rear window | | |
| | | |
| Internal | | |
| With or without tachograph * | | |
| Manual roof vent, mosquito net on vent | | |
| Rubber floor mats | | |
| Pneumatic driver's seat with seat belt, two driver's | | |
| armrests, seat belt reminder | | |
| Pneumatic passenger seat with seat belt | | |
| Fabric seat upholstery | | |
| With or without bed area [*] | | |
| Reading lamps on sideboard | | |
| Direct cabin lighting | | |
| Cabin lighting timer | | |
| Curtains around cabin area | | |
| Lights in bed area | | |
| Power windows | | |
| Electronically controlled air conditioning | | |
| Cabin air filtration, washable filter | | |
| First aid kit | | |
| English language logbook | | |
| 2 loudspeakers | | |
| Engine hour meter (records engine running times) | | |
| 2 kg fire extinguisher in the cabin, accessible from inside | | |
| and outside the cabin | | |
| | | |
| Steering wheel equipment | | |
| Easy access steering column with 3-axis adjustment | | |
| Radio player with mp3/WMA compatibility | | |
| Hands-free mobile phone interface (Bluetooth technology) | | |
| Microphone | | |

3



| Instrument panel | | |
|--|--|--|
| Minimum 7" HD color display | | |
| 12V + 24V power sockets on instrument panel, for | | |
| accessories | | |
| Remote central locking | | |
| Cruise control and speed limiter | | |
| | | |
| ELECTRONICS EQUIPMENT | | |
| Display in English and French Additional language | | |
| (Spanish) | | |
| OBD socket in cabin for data extraction and vehicle | | |
| diagnostics | | |
| Fleet management interface FMS Gateway | | |
| Rear view camera | | |
| | | |
| ELECTRICAL EQUIPMENT | | |
| Battery capacity 185 Ah | | |
| Battery kill switch (manual) | | |
| Alternator 120A | | |
| Front & rear lights system (EEC standard) | | |
| | | |
| CHASSIS / FRAME | | |
| Container twist locks: for transporting one 20" ISO | | |
| container | | |
| Frame protection paint color grey | | |
| Chassis reinforcement from the rear of the engine to the | | |
| rear of the chassis | | |
| Removable reinforced front tow bar | | |
| With and without rear underrun protection | | |
| Towing crossmember for towing hook G150 (100 x 160 | | |
| mm attachment) | | |
| Double cartridge air filtration for dusty atmosphere | | |
| Vertical exhaust pipe outlet with heat shield | | |
| | | |
| BUMPERS - STEPS AND LIGHTING | | |
| Metal sheet bumper with headlamp grid. | | |
| Retractable windscreen access steps in radiator grille and | | |
| under bumper | | |
| Electric headlamp adjustment device CEE lighting | | |
| Pre-disposal of headlamp ramp on front panel | | |
| Pre-disposal of rotating/beacon lights | | |
| | | |
| SUSPENSION | | |



| | - | | |
|--|---|----------|--|
| Front suspension: | | | |
| 3-leaf reinforced parabolic front springs | | | |
| Stabilizer bar | | | |
| | | | |
| Rear suspension: | | | |
| Elliptical leaf suspension | | | |
| Stabilizer bar | | | |
| | | | |
| | | | |
| FUEL TANK | | | |
| Steel main fuel tank approx. 500L | | | |
| Steel additional fuel tank approx. 250L | | | |
| Large capacity decanter prefilter reinforced on frame. | | | |
| Anti-syphoning system | | | |
| | | | |
| STANDARD EQUIPMENT | | | |
| On-board kit | | | |
| Tire inflator with pressure gauge (to inflate all tires of the | | | |
| vehicle) | | | |
| Jack 20 t | | | |
| Safety waistcoat | | | |
| Warning triangle | | | |
| Reverse warning buzzer | | | |
| Windscreen washer tank capacity > 8 Litres | | | |
| | | | |
| BODYWARE | | <u> </u> | |
| Flexible body mount with springs | | | |
| Orange LED parking lights with reflector | | | |
| Interface for body builder connections | | | |
| | | | |
| Service | | | |
| Fleet telematics services | | | |
| | | | |
| Various | | | |
| Maintenance schedule and spare parts list | | | |
| Maintenance literature in English, French | | | |
| Dealers and aftersales network information | | | |
| Fuel consumption information | | | |
| Training, technicians and drivers | | | |
| Diagnostics tools | | | |
| After service support, spare parts, technical hotline, | | | |
| Warranties to be granted with ICRC maintenance schedule | | | |

5



| Approval of maintenance done within ICRC in-house | | |
|---|--|--|
| workshops | | |
| Leasing options | | |
| Buy back, at the end of life | | |
| | | |
| Sustainability data to provide | | |
| The CO2 emission for vehicle production | | |
| The fuel consumption for 100km | | |
| What is the part of recycled material/components in your | | |
| production ? | | |
| The recycling percentage of the components of the vehicle | | |
| The rest of non-recyclable component (in % of weight) | | |
| The worldwide recycling networks (direct or partners) | | |
| Calcium-maintenance free batteries available ? | | |
| Greener substitute for the R134a refrigerant available | | |
| (R1234yf or similar)? | | |